# Cruiser Tram™

#### The Cruiser Tram

Specialty Vehicles is pleased to introduce the Cruiser Tram, a new people mover designed to offer an open air, street legal mode of transportation. Used for tours, excursions, or as a shuttle, the Cruiser is a great transportation solution for your guests on and off property. The tram's attractive appearance is matched with its comfortable seating and easy serviceability at your local Ford dealer. Customize your Cruiser with a variety of sizes and optional equipment to give your passengers the optimal ride.

### Cruiser Tram<sup>™</sup> Features

- 10-28 passengers
- Ford E-Series Cab & Chassis
- Gasoline, LPG, or CNG Fuel Options
- 6-Speed automatic Ford transmission
- Dual rear wheels
- Anti-corrosion treated frame
- Freedman CitiSeats
- Hard top with rain gutters
- PA system with handheld mic
- Four (4) marine grade speakers
- Anti-slip spray lined floor
- Street legal
- LED Body Lighting
- Curbside Loading
- Made in the USA

#### Optional

- ADA access packages
- Rain curtains
- Custom paint and decals
- Seat options
- Luggage/Storage Racks
- Camera System
- DVD/Monitor System
- Upgraded PA Options



#### 16 Passenger with ADA

\* Specifications are standard features only. Additional operational equipment is available. Specifications are subject to change as manufacturer determines.



**Cruiser Tram** 





440 Mark Leany Drive Henderson, NV 89011 1-800-SVI-TRAM www.specialtyvehicles.com

## Cruiser Tram<sup>™</sup> Platform



E-450 DRW Cutaway	
Wheelbase (in.)	158 - 200
Max GVW Ratings (lbs.)	14,200 (DRW w/6.2L Gas)
	14,500 (DRW w/6.8L Gas)
Max Front GAWR (lbs.)	4,600 - 5,000
Axle, Front (lbs.)	4600, Twin I-Beam IFS
Axle, Rear (lbs.)	9600, Full-Floating, Dana 10.75" HD
Brakes, Service	Power 4-wheel Disc Anti-Lock
Brake, Parking	Foot-Operated, Push to Apply/Pull Release Lever to Disengage
Alternator	155-240 Amp
Battery	72-amphr / Optional Heavy Duty 78-amphr
Engine/Horsepower/Torque	6.2L V8 FFV/331hp/356 lb.ft or 6.8L SEFI Triton V10/305hp/420 lb.ft
Frame	Single-Channel, 6 Crossmembers, 36,000 PSI Steel
Fuel Tank	55-Gallon
Shock Absorbers	Front & Rear Heavy-Duty Gas-Pressurized
Springs, Front	Coil
Springs, Rear	Multi-leaf, Single-Stage
Steering	Recirculating Ball, Power Assisted
Tires	LT225/75R16E (DRW)
Wheels	Six, 8-Hole Disc, 16" x 6.0" K Steel
Transmission	TorqShift 6-Speed Automatic Overdrive

\* Specifications are standard features only. Additional operational equipment is available. Specifications are subject to change as manufacturer determines.